

Modell:		MB 100	MB 150	MB 240	MB 240 F	MB 350	MB 450 C	MB 750	MB 1200	MB 3000 HC	MB 4000	MB 1000 AQ
Tekniska Data												
Dörrmått (mm)		360 x 380	350 x 450	550 x 750	550 x 550	550 x 1100	700 x 1100	700 x 2000	1000 x 2100	1200 x 2700	1000 x 4100	1000 x 1000
Volym (m ³)		0.15	0.22	0.35	0.36	0.46	0.73	1.56	1.76	5.4	6.35	6.35
Vikt man kan lasta i vid en förbränning		Max. 80 kg	100 kg	200 kg	200 kg	300 kg	400 kg	700 kg	1100 kg	1900 kg	4250 kg	1000 kg
Aska efter förbränning (%)		3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10	3 – 10
Förbränningstemperatur		950°C	950°C	950°C	950°C	950°C	950°C	950°C	950°C	950°C	950°C	950°C
Temperaturkontroll		Ja	Ja	Ja	Ja	Ja	Ja	Ja	Ja	Ja	Ja	Ja
Bränsle		Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas	Olja/Gas
Bränsleförbrukning eldningsolja ¹ (l/hr)		4 – 6	4 – 6	4 – 6	4 – 6	6 – 8	6 – 8	6 – 8	9 – 11.4	-	28 – 32	6 – 13
Bränsleförbrukning naturgas ¹ (Nm ³)		7 – 9	7 – 9	7 – 9	7 – 9	7.5 – 9.5	7.5 – 9.5	7.5 – 9.5	7.5 – 9.5	-	40 – 50	9 – 14
Bränsleförbrukning propangas ¹ (l/hr)		6 – 8	6 – 8	6 – 8	6 – 8	6 – 8	6 – 8	6 – 8	7.5 – 9.5	-	36 – 46	12 – 16
Volt		240	240	240	240	240	240	240	240	240	240	240
Elförbrukning (kW/h)		0.25	0.25	0.25	0.25	0.4	0.4	0.4	0.6	1	1.5	0.3
Utvändigt mått	L (mm)	1400	700	1660	1700	2300	2300	3110	3100	3600	6280	2850
	B (mm)	1100	900	1300	1500	1500	1800	1800	2500	2500	1785	1900
	H (mm)	2600	2700	1900	1900	1950	3300	3300	3300	3000	3815	2400
Invändigt mått	L (mm)	800	430	1000	1000	1300	1300	2100	2200	3000	5500	1250
	B (mm)	400	430	550	550	550	700	700	1000	1200	1050	1250
	H (mm)	500	800	640	650	650	800	800	800	1000	1050	900
Transportmått	L (mm)	1200	3000	1500	1550	2150	2150	3150	3150	5000	6100+1326 ²	2650+800 ²
	B (mm)	875	1000	1200	1000	1050	1250	1250	1500	2500	1050+1326 ²	1570+1410 ²
	H (mm)	2355	1000	1830	1830	2050	2200	2200	2100	1500	1050+1665 ²	1400+1570 ²
Vikt (kg)		1200	1500	1400	1400	2500	3500	4000	6000	8500	7600	5300

² 2 delar
